


# PEMKO® EDGING URBAN MILL FINISHED ALUMINIUM

P5  
GRIP

TYPE	Edging
RANGE	Designer Stair Edging
DESIGN	Urban
MATERIAL	6063 T5 extruded aluminium alloy with silicon carbide infill
FINISH	Mill Finished



## FEATURES

Intermittent striations of hard wearing, solid silicon carbide inserted into aluminium extrusions designed by DTAC in Australia

Available in exclusive premium quality flat or angle profiles

Suitable for all stable finished outdoor or indoor surfaces and substrates

Complies with Disability (Access to Premises—Buildings) Standards to meet the deemed-to-satisfy-provisions

Complies with slip resistance requirements as detailed in HB 198

Backed by 2 year warranty

## SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 198 (HB 198), a Guide to the specification and testing of slip resistance of pedestrian surfaces. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST	AS 4586 APPENDIX A: Wet Pendulum Test
FOUR S 96 SLIDER	= 77 CLASS = P5
TEST	AS 4586 APPENDIX B: Dry Floor Friction Test
MEAN COF	= 0.75 CLASS = D1
TEST	AS 4586 APPENDIX C: Wet/Barefoot Ramp Test
MEAN ANGLE OF INCLINATION	= 37° CLASS = C
TEST	AS 4586 APPENDIX D: Oil/Wet Ramp Test
CORRECTED MEAN OVERALL ACCEPTANCE ANGLE	= 33° CLASS = R12

## LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC EDGING, see: AS 1428.1:2009. DTAC can test your substrate for luminance contrast to give you peace of mind that your DTAC project will be fully compliant to AS 1428.1 Appendix B.

TEST	AS 1428.1 APPENDIX B PARAGRAPH B3
BLACK	
LUMINANCE REFLECTANCE RATING / WET	= 2.6
LUMINANCE REFLECTANCE RATING / DRY	= 3.6
YELLOW	
LUMINANCE REFLECTANCE RATING / WET	= 42.9
LUMINANCE REFLECTANCE RATING / DRY	= 45.0

## FIRE TESTING

Important information: The results displayed in this document relate to the behaviour and environment of the product in the conditions to which the test was carried out. This is not intended to be the sole criterion for assessing the potential fire hazard of the product in use.

TEST	AS/ISO 9239.1: Reaction to Fire Tests for Floor Coverings
MEAN DISTANCE OF FLAME TRAVEL	= 5mm
AVERAGE CRITICAL RADIANT FLUX	= ≥ 11kW/m2
AVERAGE INTEGRATED SMOKE VALUE	= 2% x min

DTAC PTY LTD  
ABN 41 093 070 127

Unit 4, 11-12 Phillip Court  
Port Melbourne Victoria  
Australia 3207

PO Box 5059  
South Melbourne Victoria  
Australia 3205

PEMKO®

T 1300 793 478


estimating@dtac.com.au  
www.dtac.com.au

© DTAC Pty Ltd 2022

# PEMKO® EDGING URBAN FINISHES & SIZES


## DESIGNER STAIR EDGING - AVAILABLE SIZES

### MILL FINISHED



**CODE** DE0730MF

**SIZE** H35 x W95 x T5 - L3000





**CODE** DE0750MF

**SIZE** H10 x W75 x T5 - L3000

### AVAILABLE FINISHES

#### MILL FINISHED WITH BLACK INFILL



**CODE** DE0740MF


**SIZE** H35 x W135 x T5 - L3000



**CODE** DE0760MF

**SIZE** W50 x T5 - L3200

#### MILL FINISHED WITH YELLOW INFILL




**CODE** DE0760MFY


**SIZE** W50 x T5 - L3000

# PEMKO® EDGING URBAN INSTALLATION & APPLICATION


## SUBSTRATE Stone / Masonry / Timber / Vinyl




**FIXING** Adhesive. Optional screw-fix (colour matched screws and plugs supplied)



**FIXING** Adhesive. Optional screw-fix (colour matched screws and plugs supplied)




**FIXING** Adhesive. Optional screw-fix (colour matched screws and plugs supplied)




**FIXING** Adhesive. Optional screw-fix (colour matched screws and plugs supplied\*)


## SUBSTRATE Vitrified Porcelain / Ceramics / Glass / Metals




**FIXING** Adhesive. Optional screw-fix (colour matched screws and plugs supplied)



**FIXING** Adhesive. Optional screw-fix (colour matched screws and plugs supplied)



**FIXING** Adhesive. Optional screw-fix (colour matched screws and plugs supplied)



**FIXING** Adhesive. Optional screw-fix (colour matched screws and plugs supplied\*)

**NOTE** Ensure grout line is discrete as illustrated

**NOTE** Ensure grout line is discrete as illustrated

\*Colour matched screws for DE0760MF only.