

PEMKO® EDGING RUGGEDTM

FIBRE GLASS REINFORCED POLYMER



TYPE	Edging	
RANGE	Stair Edging	
DESIGN	Rugged™	
MATERIAL	Fibre Glass Reinforced Polymer	
FINISH	Yellow or Black	



FEATURES

Continuous band of hard wearing, fibre glass reinforced polymer extrusion

Available in exclusive premium quality angle profiles

Suitable for all stable finished outdoor or indoor surfaces and substrates

Complies with the NCC (D3.3 Parts of buildings to be accessible) where stated and Disability (Access to Premises—Buildings) Standards to meet the deemed-to-satisfy-provisions

Complies with slip resistance requirements as detailed in HB 198

Backed by 2 year warranty

SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 198 (HB 198), a Guide to the specification and testing of slip resistance of pedestrian surfaces. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST	AS 4586 APPENDIX A: Wet Pendulum Test	
FOUR S 96 SLIDER	= 72 CLASS = P5	

LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC EDGING, see: AS 1428.1:2009. DTAC can test your substrate for luminance contrast to give you peace of mind that your DTAC project will be fully compliant to AS 1428.1 Appendix B.

TEST	AS 1428.1 APPENDIX B PARAGRAPH B3	
YELLOW		
LUMINANCE REFLECTANCE RATING / WET		= 39.5
LUMINANCE REFLECTANCE RATING / DRY		= 36.9
BLACK		
LUMINANCE REFLECTANCE	RATING / WET	= 6.6
LUMINANCE REFLECTANCE	RATING / DRY	= 7.6

DTAC PTY LTD ABN 41 093 070 127

Unit 4, 11-12 Phillip Court Port Melbourne Victoria Australia 3207

PO Box 5059 South Melbourne Victoria Australia 3205 PEMK0®

T 1300 793 478 F 1300 780 628

estimating@dtac.com.au www.dtac.com.au

© DTAC Pty Ltd 2022

H10 x W70 x T3 - L3200



PEMKO® EDGING RUGGED™

FINISHES & SIZES

CODE DEFO010Y

H10 x W70 x T3 - L3200

SIZE

TO BLACK TO TO THE TOTAL TO THE TOTAL TO THE TOTAL TO

CODE DEFO010B

SIZE

AVAILABLE FINISHES

YELLOW



BLACK





PEMKO® EDGING RUGGED™

INSTALLATION & APPLICATION

SUBSTRATE

Stone / Masonry / Timber / Vinyl



FIXING Adhesive

SUBSTRATE

Vitrified Porcelain / Ceramics / Glass




FIXING Adhesive

NOTE Ensure grout line is discrete as illustrated

SUBSTRATE

Metals



FIXING Screw-fixed.

NOTE Screw-fixed onto metal stairs and gratings (fixings not supplied).