

# PEMKO® EDGING RUGGED™ FIBRE GLASS REINFORCED POLYMER



<b>TYPE</b>	Edging
<b>RANGE</b>	Stair Edging
<b>DESIGN</b>	Rugged™
<b>MATERIAL</b>	Fibre Glass Reinforced Polymer
<b>FINISH</b>	Yellow or Black



## FEATURES

- Continuous band of hard wearing, fibre glass reinforced polymer extrusion
- Available in exclusive premium quality angle profiles
- Suitable for all stable finished outdoor or indoor surfaces and substrates
- Complies with the NCC (D3.3 Parts of buildings to be accessible) where stated and Disability (Access to Premises—Buildings) Standards to meet the deemed-to-satisfy-provisions
- Complies with slip resistance requirements as detailed in HB 198
- Backed by 2 year warranty

## SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 198 (HB 198), a Guide to the specification and testing of slip resistance of pedestrian surfaces. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

<b>TEST</b>	AS 4586 APPENDIX A: Wet Pendulum Test
<b>FOUR S 96 SLIDER</b>	= 72 <b>CLASS</b> = P5

## LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC EDGING, see: AS 1428.1:2009. DTAC can test your substrate for luminance contrast to give you peace of mind that your DTAC project will be fully compliant to AS 1428.1 Appendix B.

<b>TEST</b>	AS 1428.1 APPENDIX B PARAGRAPH B3
<b>YELLOW</b>	
<b>LUMINANCE REFLECTANCE RATING / WET</b>	= 39.5
<b>LUMINANCE REFLECTANCE RATING / DRY</b>	= 36.9
<b>BLACK</b>	
<b>LUMINANCE REFLECTANCE RATING / WET</b>	= 6.6
<b>LUMINANCE REFLECTANCE RATING / DRY</b>	= 7.6

DTAC PTY LTD  
ABN 41 093 070 127

Unit 4, 11-12 Phillip Court  
Port Melbourne Victoria  
Australia 3207

PO Box 5059  
South Melbourne Victoria  
Australia 3205

PEMKO®

T 1300 793 478  
F 1300 780 628


estimating@dtac.com.au  
www.dtac.com.au

© DTAC Pty Ltd 2020

# PEMKO® EDGING RUGGED™ FINISHES & SIZES

## DESIGNER STAIR EDGING - AVAILABLE SIZES

### YELLOW



CODE DEF0010Y

SIZE H10 x W70 x T3 - L1500

NCC COMPLIANT


### BLACK



CODE DEF0010B

SIZE H10 x W70 x T3 - L1500

NCC COMPLIANT



CODE DEF0020Y

SIZE H10 x W70 x T3 - L1800

NCC COMPLIANT



CODE DEF0020B

SIZE H10 x W70 x T3 - L1800

NCC COMPLIANT

### AVAILABLE FINISHES

#### YELLOW




#### BLACK



# PEMKO® EDGING RUGGED™ INSTALLATION & APPLICATION

**SUBSTRATE** Stone / Masonry / Timber / Vinyl



**FIXING** Adhesive

**NCC COMPLIANT**

**SUBSTRATE** Vitrified Porcelain / Ceramics / Glass




**FIXING** Adhesive

**NOTE** Ensure grout line is discrete as illustrated

**NCC COMPLIANT**

**SUBSTRATE** Metals



**FIXING** Screw-fixed.

**NOTE** Screw-fixed onto metal stairs and gratings (fixings not supplied).

**NCC COMPLIANT**