

BLACK TOP TERRACED WARNING TACTILE

P5
GRIP

PRODUCT CODES: DESCRIPTION:

DT0210 SPIKED

DT0211 FLAT

RANGE Warning Tactile

DESIGN Terraced Black Top

MATERIAL 316 marine grade stainless steel / UV stabilised thermo plastic urethane (TPU)

LOCATION Indoor or outdoor

DIMENSIONS OUTER DIA: 35mm TOP DIA: 25mm
THICKNESS: 5mm



FEATURES & BENEFITS

Machined, concentric circle design on the horizontal face with a terraced slip resistant outer edge

Complies with the NCC [D4D9 Tactile Indicators] and Disability (Access to Premises—Buildings) standards to meet the deemed-to-satisfy-provisions

Complies with slip resistance requirements as detailed in HB 198

SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 198 (HB 198), a Guide to the specification and testing of slip resistance of pedestrian surfaces. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST AS 4586 APPENDIX A: Wet Pendulum Test

FOUR S 96 SLIDER = 103 CLASS = P5

TRL 55 SLIDER = 83 CLASS = P5

TEST AS 4586 APPENDIX C: Wet/Barefoot Ramp Test

MEAN ANGLE OF INCLINATION = >35° CLASS = C

TEST AS 4586 APPENDIX D: Oil/Wet Ramp Test

CORRECTED MEAN OVERALL ACCEPTANCE ANGLE = 26.2° CLASS = R11

LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC TGSI, see: AS/NZS 1428.4.1:2009.


TEST AS/NZS 1428.4.1 APPENDIX E PARAGRAPH E3

LIGHT REFLECTANCE VALUE / WET = 3.52

LIGHT REFLECTANCE VALUE / DRY = 3.83

BLACK TOP TERRACED WARNING TACTILE INSTALLATION & APPLICATION


SUBSTRATE Stone / Masonry / Timber / Vinyl



CODE DT0210


FIXING Drill and pressure fit
(M8 x 25mm hole)

SUBSTRATE Vitrified Porcelain / Ceramics / Glass / Metals



CODE DT0210

FIXING Drill and pressure fit
(M8 x 25mm hole)



CODE DT0211

FIXING Adhesive