

# BRASS CLASSIC ECOTAC® WARNING TACTILE (SPIKED)



PRODUCT CODES: DESCRIPTION:
-----------------------------

DT0312	SPIKED		
RANGE	Warning Tactile		
DESIGN	Classic Ecotac®		
MATERIAL	Solid brass		
LOCATION	Indoor or outdoor		
DIMENSIONS	OUTER DIA: 35mm TOP DIA: 25mm THICKNESS: 5mm		



## **FEATURES & BENEFITS**

Machined, concentric circle design on the horizontal face with a smooth outer edge  $\,$ 

An environmentally friendly alternative to the solid classic tactile, featuring a cupped underside that uses less stainless steel putting less demand on resources

Complies with the NCC (D4D9 Tactile Indicators) and Disability (Access to Premises—Buildings) standards to meet the deemed-to-satisfy-provisions

Complies with slip resistance requirements as detailed in HB 198

Identifiable by the unique "double lip" design, providing a distinct advantage when it comes to high slip resistance

## **SLIP RESISTANCE TESTING**

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 198 (HB 198), a Guide to the specification and testing of slip resistance of pedestrian surfaces. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST	AS 4586 APPENDIX A: Wet Pendulum Test	
FOUR S 96 SLIDER	= 106 <b>CLASS</b> = P5	
TRL 55 SLIDER	= 83 <b>CLASS</b> = P5	
TEST	AS 4586 APPENDIX C: Wet/Barefoot Ramp Test	
MEAN ANGLE OF INCI	<b>INATION</b> = $27^{\circ}$ <b>CLASS</b> = C	
TEST	AS 4586 APPENDIX D: Oil/Wet Ramp Test	
CORRECTED MEAN O	ERALL ACCEPTANCE ANGLE = 33° CLASS = R12	

## **LUMINANCE TESTING**

Important information: To determine a luminance contrast between a substrate and the DTAC TGSI, see: AS/NZS 1428.4.1:2009.

TEST	AS/NZS 1428.4.1 APP	ENDIX E PARAGRAPH E3
LIGHT REFLECTANCE VALUE / WET		= 52.90
LIGHT REFLECTAN	CE VALUE / DRY	= 55.09




## BRASS CLASSIC ECOTAC® WARNING TACTILE (SPIKED)

INSTALLATION & APPLICATION

## SUBSTRATE

Stone / Masonry / Timber / Vinyl




CODE DT0312

FIXING Drill and pressure fit (M8 x 25mm hole)

## SUBSTRATE

Vitrified Porcelain / Ceramics / Glass / Metals



CODE DT0312

FIXING Drill and pressure fit (M8 x 25mm hole)

## THE DTAC DIFFERENCE

 $\label{limited} DTAC \ Warning \ Tactiles \ are \ identifiable \ by \ the \ unique \ "double \ lip" \ design, \ providing \ a \ distinct \ advantage \ when \ it \ comes \ to \ high \ slip \ resistance.$ 

Warning Tactile's are a series of raised dots that are installed on pedestrian surfaces. They assist in the orientation of the vision impaired and give tactile warning so they may safely navigate the built environment.

With an extensive range of designs and colours, DTAC work closely with architects, specifiers and builders to exceed design and aesthetic expectations on every project.

- Available in a range of colours and designs to suit all applications
- Solutions for all stable surfaces and substrates
- Designed to comply with building codes and regulations
- Tested for luminance and slip resistance requirements.