

STAINLESS STEEL TERRACED ECOTAC® WARNING TACTILE (SPIKED)

P5
GRIP

PRODUCT CODES: DESCRIPTION:

DT0130 SPIKED

RANGE	Warning Tactile
DESIGN	Terraced Ecotac®
MATERIAL	316 marine grade stainless steel
LOCATION	Indoor or outdoor
DIMENSIONS	OUTER DIA: 35mm TOP DIA: 25mm THICKNESS: 5mm



FEATURES & BENEFITS

Machined, concentric circle design on the horizontal face with a terraced slip resistant outer edge

An environmentally friendly alternative to the solid classic tactile, featuring a cupped underside that uses less stainless steel putting less demand on resources

Identical to the DTAC solid tactile when installed

Complies with the NCC (D4D9 Tactile Indicators) and Disability (Access to Premises—Buildings) standards to meet the deemed-to-satisfy-provisions

Complies with slip resistance requirements as detailed in HB 198

SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 198 (HB 198), a Guide to the specification and testing of slip resistance of pedestrian surfaces. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST	AS 4586 APPENDIX A: Wet Pendulum Test
FOUR S 96 SLIDER	= 95 CLASS = P5
TRL 55 SLIDER	= 74 CLASS = P5
TEST	AS 4586 APPENDIX C: Wet/Barefoot Ramp Test
MEAN ANGLE OF INCLINATION	= 27° CLASS = C
TEST	AS 4586 APPENDIX D: Oil/Wet Ramp Test
CORRECTED MEAN OVERALL ACCEPTANCE ANGLE	= 29° CLASS = R12


LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC TGSI, see: AS/NZS 1428.4.1:2009.

TEST	AS/NZS 1428.4.1 APPENDIX E PARAGRAPH E3
LIGHT REFLECTANCE VALUE / WET	= 47.73
LIGHT REFLECTANCE VALUE / DRY	= 50.65

STAINLESS STEEL TERRACED ECOTAC® WARNING TACTILE (SPIKED) INSTALLATION & APPLICATION


SUBSTRATE Stone / Masonry / Timber / Vinyl



CODE DT0130

FIXING Drill and pressure fit
(M8 x 30mm hole)

SUBSTRATE Vitrified Porcelain / Ceramics / Glass / Metals



CODE DT0130

FIXING Drill and pressure fit
(M8 x 25mm hole)