

PEMKO® RUGGED™ EDGING 10X70X3MM



PRODUCT CODES: DESCRIPTION:

Indoor or outdoor

LOCATION

DEF0010B	BLACK	
RANGE	Stair Nosing & Edging	
DESIGN	Rugged™	
MATERIAL	Fibre Glass Reinforced Polymer	

FEATURES & BENEFITS

Continuous band of hard wearing, fibre glass reinforced polymer extrusion

Available in exclusive premium quality angle profiles

Suitable for all stable finished outdoor or indoor surfaces and substrates

Complies with the NCC (D4D4 Parts of buildings to be accessible) where stated and Disability (Access to Premises—Buildings) Standards to meet the deemed-to-satisfy-provisions

Complies with slip resistance requirements as detailed in HB 198

SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 198 (HB 198), a Guide to the specification and testing of slip resistance of pedestrian surfaces. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST	AS 4586 APPENDIX A: Wet Pendulum Test
FOUR S 96 SLIDER	= 72 CLASS = P5

LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC EDGING, see: AS 1428.1:2009.

TEST	AS 1428.1 APPENDIX B PARAGRAPH B3
LIGHT REFLECTANCE VALUE / WET	
LIGHT REFLECTANCE VALUE /	DRY = 2.94







PEMKO® RUGGED™ EDGING 10X70X3MM

FINISHES & SIZES

AVAILABLE FINISHES & SIZES

BLACK





CODE DEF0010B

SIZE H10 x W70 x T3 - L3200mm



PEMKO® RUGGED™ EDGING 10X70X3MM

INSTALLATION & APPLICATION

SUBSTRATE

Stone / Masonry / Timber / Vinyl



CODE DEF0010B

FIXING Adhesive

SUBSTRATE

Vitrified Porcelain / Ceramics / Glass




CODE DEF0010B

FIXING Adhesive

NOTE Ensure grout line is discrete as illustrated

SUBSTRATE

Metals



CODE DEF0010B

FIXING Screw-fixed

NOTE Screw-fixed onto metal stairs and gratings (fixings not supplied).