DTAC

# PEMKO® URBAN EDGING 10X65X5MM (WHITE)



#### **PRODUCT CODES:**

**DE0700W** 

NATURAL ANODISED

White silicon carbide infill

**DESCRIPTION:** 

RANGE	Stair Nosing & Edging
DESIGN	Urban
MATERIAL	6063 T5 extruded aluminium alloy with silicon carbide infill
LOCATION	Indoor or outdoor

#### **FEATURES & BENEFITS**

Continuous band of hard wearing, solid silicon carbide inserted into aluminium extrusions designed by DTAC in Australia

Available in an exclusive premium quality angle profile

Suitable for all stable finished outdoor or indoor surfaces and substrates

Complies with the NCC (D4D4 Parts of buildings to be accessible) where stated and Disability (Access to Premises—Buildings) Standards to meet the deemed-to-satisfy-provisions

Complies with slip resistance requirements as detailed in HB 198

#### SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 198 (HB 198), a Guide to the specification and testing of slip resistance of pedestrian surfaces. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST	AS 4586 APPENDIX A: Wet Pendulum Test
FOUR S 96 SLIDER	= 74 <b>CLASS</b> = P5
TRL 55 SLIDER	= 82 <b>CLASS</b> = P5

#### LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC EDGING, see: AS 1428.1:2009.

TEST	AS 1428.1 APPENDIX B PARAGRAPH B3			
LIGHT REFLECTANCE VALUE /	/ WET	= 43.80		
LIGHT REFLECTANCE VALUE /	/ DRY	= 43.58		



**DTAC PTY LTD** ABN 41 093 070 127

Unit 4, 11-12 Phillip Court Port Melbourne Victoria Australia 3207 PO Box 5059 South Melbourne Victoria Australia 3205

PEMK0® T 1300 793 478 estimating@dtac.com.au dtac.com.au

© DTAC Pty Ltd 2025


## DTAC

### PEMKO® URBAN EDGING 10X65X5MM (WHITE) FINISHES & SIZES

**AVAILABLE FINISHES & SIZES** 

SIZE

HARD NATURAL ANODISED (25µm) WITH WHITE INFILL




H10 x W65 x T5 - L3200mm

### DTAC®

### PEMKO® URBAN EDGING 10X65X5MM (WHITE) INSTALLATION & APPLICATION



Stone / Masonry / Timber / Vinyl




#### CODE DE0700W

FIXING Adhesive. Optional screw-fix (Screws\* and plugs available upon request)



### CODE DE0700W FIXING Adhesive only

### SUBSTRATE Vitrified Porcelain / Ceramics / Glass / Metals



FIXING	Adhesive. Optional screw-fix (Screws* and plugs available upon request)
NOTE	Ensure grout line is discrete as illustrated

<u> </u>			~~~		<u> </u>	
4	•		o			4
Δ.	4 °	4	, · ·	Δ	4	· 4
° 4		4		4		⊿
~		. <	' 4		۹.	

### CODE DE0700W

**FIXING** Adhesive only NOTE Ensure grout line is

discrete as illustrated