

BRASS TERRACED WARNING TACTILE

P5
GRIP

PRODUCT CODES: DESCRIPTION:

DT0310 SPIKED

DT0311 FLAT

RANGE Warning Tactile

DESIGN Terraced

MATERIAL Solid brass

LOCATION Indoor or outdoor

DIMENSIONS OUTER DIA: 35mm TOP DIA: 25mm
THICKNESS: 5mm

FEATURES & BENEFITS

Machined, concentric circle design on the horizontal face with a terraced slip resistant outer edge

Complies with the NCC [D4D9 Tactile Indicators] and Disability (Access to Premises—Buildings) standards to meet the deemed-to-satisfy-provisions

Complies with slip resistance requirements as detailed in HB 198

SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 198 (HB 198), a Guide to the specification and testing of slip resistance of pedestrian surfaces. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST AS 4586 APPENDIX A: Wet Pendulum Test

FOUR S 96 SLIDER = 85 CLASS = P5

TRL 55 SLIDER = 75 CLASS = P5

LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC TGSI, see: AS/NZS 1428.4.1:2009.

TEST AS/NZS 1428.4.1 APPENDIX E PARAGRAPH E3


LIGHT REFLECTANCE VALUE / WET = 51.37

LIGHT REFLECTANCE VALUE / DRY = 52.06



BRASS TERRACED WARNING TACTILE INSTALLATION & APPLICATION


SUBSTRATE Stone / Masonry / Timber / Vinyl



CODE DT0310


FIXING Drill and pressure fit
(M8 x 25mm hole)

SUBSTRATE Vitrified Porcelain / Ceramics / Glass / Metals



CODE DT0310

FIXING Drill and pressure fit
(M8 x 25mm hole)



CODE DT0311

FIXING Adhesive