

SILICON CARBIDE CLASSIC PVD BLACK DIRECTIONAL TACTILE



PRODUCT CODE: DIR0150

RANGE	Directional Tactile	
DESIGN	Classic Silicon Carbide	
MATERIAL	316 marine grade stainless steel with silicon carbide infill	
LOCATION	Indoor or Outdoor	



FEATURES & BENEFITS

Hard wearing, silicon carbide inserted into the horizontal face with a smooth machined outer edge

Designed to comply with AS/NZS 1428.4.1 (Section 3.2 Directional TGSI's)

Complies with the NCC (D4D9 Tactile Indicators) and Disability (Access to Premises—Buildings) standards to meet the deemed-to-satisfy-provisions

Complies with slip resistance requirements as detailed in HB 198

SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 198 (HB 198), a Guide to the specification and testing of slip resistance of pedestrian surfaces. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST	AS 4586 APPENDIX A: Wet Pendulum Test	
TRL 55 SLIDER	= 64 CLASS = P5	

LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC TGSI, see: AS/NZS 1428.4.1:2009.

TEST	AS/NZS 1428.4.1 APPEN	DIX E PARAGRAPH E3
LIGHT REFLECTANCE VALUE / WET = 4.76		
LIGHT REFLECTANCE VALUE / DRY = 4		= 4.96






SILICON CARBIDE CLASSIC PVD BLACK DIRECTIONAL TACTILE

INSTALLATION & APPLICATION

SUBSTRATE

Stone / Masonry / Timber / Vinyl




CODE DIR0150

FIXING Drill and pressure fit (M8 x 25mm hole)

SUBSTRATE

Vitrified Porcelain / Ceramics / Glass / Metals



CODE DIR0150

FIXING Drill and pressure fit (M8 x 25mm hole)

SIDE PROFILE

CODE DIR0150

SIZE L290 x W35 x H5mm